



SPECIFICATIONS

Product Description: **VENTILATION BLOWER, STANDARD**
Part Number: **9504**
Style: **CENTRIFUGAL FAN**

GENERAL DESCRIPTION:

Smart Compact design allows for easy use and storage without sacrificing airflow. Two 8" ports offer positive ventilation or fume extraction. The electric motor is cage-enclosed for protection. Works great with generators. Air delivery certified CEESI.

CONSTRUCTION:

- 8" flange on intake and exhaust ports
- Tough "safety orange" polyethylene construction
- One piece housing with integrated handle
- Powder coated 16 gauge steel housing
- Steel base with expanded metal on sides
- Steel zinc plated grill
- Equipped with four rubber feet

MOTOR:

HP: 1/3 HP
Certifications: UL Recognized, CSA Certified
Voltage/Hz: 115 VAC, 60Hz, single Ø
RPM: 1725
Current Draw: 6A (Loaded at 120 Volts, 60 Hz)
Cord: 6' SJTW, 16/3 AWG, 90C 300V medium duty
Switch: Toggle ON/OFF with guard
Plug: NEMA 5-15P three prong plug



FAN:

- Steel wheel with aluminum hub

DUCTING: (Optional)

- Retractable, non-collapsible design
- Single-PVC, PVC coated, vinyl and polyester materials, temperature resistant up to 108° F
- Yellow color with black weather-strip and integrated nylon straps
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

DIMENSIONS:

Length	Width	Height	Weight
16"	18 ½"	20"	38 lbs

FLOW RATES: (CFM calculated using 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
1066 CFM	839 CFM	745 CFM