

SPECIFICATIONS

Product Description: **VENTILATION BLOWER, STANDARD**
 Part Number: **9515**
 Style: **AXIAL FAN 16" (40.6cm)**

GENERAL DESCRIPTION:

For applications requiring a large amount of output. Standard is a ½ HP motor with an efficient six-blade impeller in a rugged metal housing. Certified to CSA Standard C22.2 No.113.

CONSTRUCTION:

- Complete unit epoxy powder coated in orange
- Interchangeable flange for intake or exhaust side mounting
- 18 gauge cold rolled steel housing
- Integrated carrying handles on four sides
- Steel/chrome plated grill
- Equipped with four rubber feet
- Stackable design
- Can be used with Adaptor Reducer (PN: 9600-50) used with 8" (20.3cm) duct



MOTOR:

HP: ½ HP
 Certifications: UL Recognized, CSA Certified
 Voltage/Hz: 115V AC, 60 Hz, Single Ø
 RPM : 1725
 Current Draw: 7.2 A
 Cord: 25' (7.62m) 16/3 AWG, SJTW 90C 300V medium duty
 Plug: NEMA 5-15 (Grounded three-prong)

FAN:

- Glass reinforced Polypropylene (PPG) six blade fan, with aluminum hub
- Moving fan mounted 1 5/8" (4.12cm) from grill for safety, grill gap-5/16" (.79cm)

DUCTING:

- Retractable, non-collapsible design
- Single-ply, PVC coated, vinyl and polyester materials, temperature resistant up to 180°F (82.2°C)
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

BLOWER DIMENSIONS:

Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
18" (45.7)	18" (45.7)	19" (48.2)	47 lbs (21.3)

FLOW RATES: (CFM calculated using 15' (4.57m) of 16" (40.6cm) ducting)

Free Air CFM (m³/hr)	One 90° Bend CFM (m³/hr)	Two 90° Bends CFM (m³/hr)
3400 (5776.63)	2800 (4757.23)	2300 (3907.72)