



SPECIFICATIONS

Product Description: **BLOWER, COM-PAX-IAL, AC**
 Part Number: **9534, 9534-15, 9534-25**
 Style: **AXIAL FAN, COMPACT**

GENERAL DESCRIPTION:

Lightweight and compact design allows for easy portability without sacrificing performance.

CONSTRUCTION:

- Complete unit epoxy powder coated orange
- 15 Gauge cold rolled steel housing with welded motor mount construction
- 20 Gauge steel canister
- Available with 15' or 25' ducting and canister
- Enclosed wide base for greater stability
- Steel/chrome plated grill
- Carry handle made of 3-ply rubber belting
- Equipped with four rubber feet



FAN:

- Glass reinforced polypropylene (PPG) six blade fan
- Aluminum hub
- Moving fan mounted 1 5/8" from grill for safety



MOTOR:

HP: 1/3 HP
 Volts: 115 AC Single Ø
 Max RPM: 3200 (Loaded at 120 Volts, 60 Hz)
 Current Draw: 3.6A (Loaded at 120 Volts, 60 Hz)
 Capacitor: 7.5 MFD 370V AC
 Cord: 6' SJOOW 16/3 AWG neoprene, 300V medium duty
 Plug: NEMA 5-15 125V AC

BLOWER DIMENSIONS:

Description	Part No	Length	Width	Height	Weight
Blower only	9534	12"	8"	10"	17 lbs
Blower w/15' Duct Canister	9534-15	28"	11"	10"	34 lbs
Blower w 25' Duct Canister	9534-25	28"	11"	10"	37 lbs

FLOW RATES CEESI TESTED: (CFM calculated using 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
778 CFM	645 CFM	496 CFM