

SPECIFICATIONS

Product Description: **8" PLASTIC COM-PAX-IAL BLOWER EXPLOSION PROOF**
 Part Number: **9538 Series**
 Style: **AXIAL FAN 8" WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' or 25' of statically conductive ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation. It is designed for explosion proof environments

CONSTRUCTION:

- Polyethylene housing and canister assembly
- Lightweight, corrosion, UV and chemical resistant
- Super quiet, "safety orange"
- Bottom enclosure to protect electrical components
- Carry handle molded into blower and canister housing
- Steel powder coated grill



MOTOR:

HP: 1/3
 Voltage/Hz: 115 V, 60 Hz, Single Ø
 Max RPM: 3250
 Current Draw: 2.2A
 Cord: 25' SJOOW 18/3 AWG 300V, medium duty
 Plug: NEMA 115V, 20 amp, "ECP" type

FAN:

- Polypropylene six blade fan
- Aluminum hub

DUCTING: (included on 9538-15 and 9538-25 models)

- Black single-ply lightweight vinyl/polyester, coated with neoprene 250°F temperature resistant
- Non-collapsible retractable design, Class 1 hard drawn spring steel wire helix

HAZARDOUS LOCATION RATINGS:

Class: I	Class: II
Divisions: 1 & 2	Division: 1 & 2
Groups: C & D	Groups: F & G

BLOWER DIMENSIONS:

Description	Blower P/N	Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
Blower only	9538	13 ¼" (33.6)	12" (30.4)	13 ¾" (34.9)	20 lbs (9)
Blower w/15' Duct & Canister	9538-15	34 ½" (87.6)	13 ½" (34.2)	14 ¾" (37.4)	37 lbs (16.7)
Blower w/25' Duct & Canister	9538-25	34 ½" (87.6)	13 ½" (34.2)	14 ½" (36.8)	44 lbs (19.9)

FLOW RATES: (CFM calculated using 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
900 CFM	650 CFM	625 CFM