



SPECIFICATIONS

Product Description: **AIR CART**
Part Number: **9885-01**
Style: **LOW PRESSURE**

GENERAL DESCRIPTION:

Used for short duration jobs, with up to one hour of air. It is an ideal mobile primary or emergency air supply. Used with pressure demand respirators. It accepts standard 30 minute SCBA bottles.

CONSTRUCTION:

- Steel frame and handle
- Powder coated white
- Two extra large rubberized wheels
- Two front rubber feet for support
- Dual extra-wide nylon cylinder straps
- Rubber handle

CYLINDERS:

- DOT 3AL 2216
- CGA 346
- Aluminum construction
- 30 minute
- 45 cu ft
- 2216 PSI (152.78 bar)

PLUMBING ASSEMBLY:

Regulator: Brass, nickel chrome plated
Pressure Gauges: 2" (5.0cm) face analog
Coupler: Hansen, brass Quick-Connect 1/4" (.63cm)
Materials: Brass
Alarm: Aluminum block, Activated @ 550 psi (37-92 bar) and below
Check Valve: Inline, Brass

ACCESSORIES:

Manifold, 5 outlet: P/N: 9891-05 (with Hansen couplers)
Manifold, 5 outlet: P/N: 989 1-22 (with Schrader couplers & Hansen plug)
Bypass Assembly: P/N: 9885-46 (with CGA 346)





SPECIFICATIONS

Product Description: **AIR CART**
Part Number: **9886-01**
Style: **HIGH PRESSURE**

GENERAL DESCRIPTION:

Used for short duration jobs, with up to two hours of air. It is an ideal mobile primary or emergency air supply. Used with pressure demand respirators. It accepts standard 30, 45 and 60-minute SCBA bottles.

CONSTRUCTION:

- Steel Frame and handle, powder coated white
- Two extra large rubberized wheels with two rubber feet for support
- Dual extra-wide nylon cylinder straps
- Rubber handle

CYLINDERS:

- DOT E 9634-4500
- CGA 347
- Aluminum construction
- Fiberglass full wrapped
- 60 minute
- 4500 psi (310.26 bar) - 6000 psi (413.68 bar) maximum

PLUMBING ASSEMBLY:

Regulator: Brass, Nickel chrome plated
Gauges: 2" (5.0cm) face analog in psi
Coupler: Hansen, Brass Quick-Connect 1/4" (.63cm)
Materials: Brass
Alarm: Aluminum block
Activated @ 550 psi (37.92 bar) and below
Check Valve: Inline, Brass

ACCESSORIES:

Manifold, 5 outlet: P/N: **9891-05** (with Hansen couplers)
Manifold, 5 outlet: P/N: **9891-22** (with Schrader couplers)
Bypass Assembly: P/N: **9886-46** (with CGA 347)

