



SPECIFICATIONS

Product Description: **D-2 MOLD LITE SAMPLER**
Part Number: **9800 WITH STAND, 9800-88 WITHOUT STAND**
Style: **DIAPHRAGM**

GENERAL DESCRIPTION:

This low maintenance oscillating pump is designed for use with all mold sampling cassettes and impactors. It is lightweight, quiet performance, and easy to use. It has a built in adjustable flow meter/ regulator and rubber suction cup feet to prevent the pump from moving while in use. The pump is available as a kit (P/N 9800) with an adjustable tripod stand.

CONSTRUCTION:

- Rigid metal housing
- Powder coated (Gray color)
- Built in plumbing
- Adjustable flow meter/regulator
- Built in handle
- Rubber suction cup feet
- On/Off switch on handle, less breakage



PUMP:

Type: Oscillating double diaphragm
Performance: 3-33 LPM (liters per minute)

MOTOR:

Specs: 115 VAC, Single Phase, 60 Hz .45 Amps
Inlet Filter: 40.0 Micron bronze/steel
Cord: 6.5' (1.95m) 18 AWG
Switch: ON/OFF Switch built into handle
Plug: Integrated NEMA 5-15

OPTIONAL:

Tripod Stand: P/N 9804
Anodized aluminum, adjustable with three extending rods

DIMENSIONS:

Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
6" (15.2 cm)	6" (15.2 cm)	6 ¼" (15.8 cm)	5.3 lbs (2.40 kg)