



## SPECIFICATIONS

Product Description: **CO MONITOR**  
 Part Number: **9871-02**  
 Style: **REMOTE**

### GENERAL DESCRIPTION:

Attached to any air source or filter panel. To meet OSHA requirements an optional CO monitor is available for continuous monitoring of carbon monoxide levels.

### CONSTRUCTION:

- Housed in a portable, rugged Pelican case with handle and latches for protection and security
- Airline pigtail and coupling kit for fast and easy adaptation to an existing air filtration system
- All brass plumbing with quick-disconnect ¼" (.63cm) Hansen plug



### CO MONITOR:

Power Source: 115V AC to 9V DC power adapter for continuous power supply  
 9V DC Alkaline battery (primary or as back-up for AC adapter)  
 Alarm Setting: 10 PPM (Canada 5 PPM)  
 External Connections: Optional Strobe Light Alarm  
 Audible: 90 decibel Piezo Alarm  
 Visual: External power LED light signal  
 Sensor: Replaceable electrochemical  
 Display: Liquid crystal  
 Keys: Mode & Set  
 Modes: Normal operation, Peak, Battery Charge and Calibration  
 Calibration: Self adjusting calibration to 20 PPM CO

### REGULATOR:

- Pressure range (5-150 PSI) (.34-10.34 bar)
- Zink body and ABS cover
- Acetal adjusting knob
- Brass/nitrile valve
- 0-160 pressure gauge

### FLOW METER:

- Clear acrylic
- Adjustable metering valve
- Range from 0.0-1.0 LPM

### DIMENSIONS:

Length In. (cm)	Width In. (cm)	Height In. (cm)	Weight Lbs. (Kg)
12" (30.4 cm)	5" (12.7 cm)	10" (25.4 cm)	6.5 lbs (2.94 kg)