



SPECIFICATIONS

Product Description: **BREATHING AIR PUMP A-1500 TE**
Part Number: **9832-E**
Style: **ROTARY VANE, 220V/50Hz**

GENERAL DESCRIPTION:

Portable air source for up to three full or half face respirator users, or two hood users. Solid performance in multi-worker applications, sanding or chemical handling operations.

CONSTRUCTION:

- Rigid metal base & housing with four rubber feet
- Brass & galvanized steel plumbing
- Quick-connect Rectus (OBAC) air fittings
- Adjustable brass pressure relief valve
- Pressure gauge 0-15 psi (0-1.03 bar)
- Fan guard
- Powder coated gray



PUMP:

**Warning: Breathing Air Pumps are not to be used with generators*

***Warning: Air inlet to the pump must be located where breathable air can be assured at all times*

Type: Oil-less, rotary vane, direct driven
Vaness: Carbon construction (4ea/replaceable) (3.5" (8.89 cm) X 1.3" (3.40 cm) X 0.188" (0.47 cm))
Inlet Filter: 50 micron felt material
Exhaust Filter: 0.3 Micron HEPA
Working Pressure: 2-12 psi (0.14-0.83 bar) (15 psi (1.03 bar) max)
Performance: 0-18 CFM (0-25.48 m³/hr) at 60 Hz (adjusted via pressure relief valve)
Airline length: 100 feet (30.4 m) maximum, from pump to respirator (sold separately)
Noise level: At Pump: 95 Db, At 6 feet (1.82 m): 85 dB, At 10 feet (3.04 m): 78 dB
Temperature Range: 32° F - 104° F (0° C - 40° C)

MOTOR:

Type: 1 ½ HP, TEFC Continuous Duty
Certifications: UL Listed, CSA Certified
Volts: 220V AC, Single Phase, 50 Hz
Current Draw: 8A @ 220V
RPM: 1425
NEMA Nom Eff: 73.0
Cord: 8' (2.43 m) 14/3 AWG SJTW-A 300V Neoprene medium duty
Switch: Toggle, external ON/OFF

DIMENSIONS:

Length	Width	Height	Weight
27" (68.5 cm)	10" (25.4 cm)	15" (38.1 cm)	122 lbs. (55.33 kg)