



SPECIFICATIONS

Product Description: **AIRLINE FILTER**
 Part Number: **9874-W/O**
 Style: **POT STYLE**

GENERAL DESCRIPTION:

The Airline Filter is designed to remove oil mist, water vapor and particulates down to 0.5 microns from breathing grade compressed air. The Airline Filter is placed inline between the breathing air source and the respirator airline hose, air enters the filter through the inlet port. Once the air has been filtered, moisture is removed and drained through a drain valve located at the bottom of the airline filter. The Airline Filter is equipped with a four-worker manifold for multiple respirator users.



CONSTRUCTION:

Body: Heavy gauge impact- and corrosion-resistant aluminum, powder coated (gray)
 Valve: Balanced valve design, Brass/Nitrile
 Relief Valve: Brass, spring loaded (External)
 Inlet: 1" NPT
 Fitting: 1/2" Quick-Connect (Hansen Style)
 Max Temp: 140° F (60° C)
 Max Pressure: 125 psi (1.72 bar)
 Pressure Gauge: Analog, 0-150 psi (0-10.34 bar)
 Legs: ABS Plastic, can be either floor or wall mounted
 Outlet Ports: 4 ea. 1/4" Hansen couplers (Std.)

FILTER CARTRIDGE: (P/N 3100-02)

- Replaceable
- 3 Stage: Traps oil, dust particles and odors from compressed air source
- Large capacity
- Provides better and longer filtrations
- Material: Felt, polyester wadding; Activated carbon; Activated alumina



DIMENSIONS:

Height In. (cm)	Length In. (cm)	Depth In. (cm)	Weight Lbs. (Kg)
18 ¾" (47.6)	12 ¼" (31.1)	12 ¼" (31.1)	16 lbs (7.2)

**** THE ALLEGRO AIRLINE FILTER DOES NOT REMOVE CARBON MONOXIDE (CO) OR TOXIC GASES****