



SPECIFICATIONS

Product Description: **BREATHING AIR PUMP A-1500 EX**
 Part Number: **9833**
 Style: **ROTARY VANE, EXPLOSION-PROOF**

GENERAL DESCRIPTION:

Portable explosion proof air source for up to three full or half face respirator users, or two hood users. Solid performance in multi-worker applications, sanding or chemical handling operations.



CONSTRUCTION:

- Rigid metal base & housing with four rubber feet
- Brass & galvanized steel plumbing
- Quick-connect Rectus (OBAC) air fittings
- Adjustable brass pressure relief valve
- Pressure gauge 0-15 psi (0-1.03 bar)
- Fan guard
- Powder coated gray

PUMP:

**Warning: Breathing Air Pumps are not to be used with generators*

***Warning: Air inlet to the pump must be located where breathable air can be assured at all times*

Type: Oil-less, rotary vane, direct driven
 Vanes: Carbon construction (4ea/replaceable) (3.5" (8.89 cm) X 1.3" (3.40 cm) X 0.188" (.47 cm))
 Inlet Filter: 50 micron felt material
 Exhaust Filter: 0.3 Micron HEPA
 Working Pressure: 2-12 psi (0.14-0.83 bar) (15 psi (1.03 bar) max)
 Performance: 0-15 CFM (0-25.48 m³/hr) at 60 Hz (adjusted via pressure relief valve)
 Airline length: 100 feet (30.4m) maximum, from pump to respirator (sold separately)
 Noise level: At Pump: 95 dB
 At 6 feet (1.82 m): 85 dB
 At 10 feet (3.04 m): 78 dB
 Temperature Range: 32° F - 104° F (0° C - 40° C)

MOTOR:

Type: 1 1/2 HP, XPFC continuous duty
 Certifications: UL Listed, CSA Certified
 Volts: 115V/230 VAC, Single Phase, 60 Hz
 Current Draw: 16A @ 115V (8A @ 230V)
 RPM: 1725
 NEMA Nom Eff: 75.0
 Cord: 25' (7.62 m) 12 AWG SOOW Extra Hard Usage
 Plug: 20A 125V AGP Type, hazardous location

HAZARDOUS LOCATION:

Class: I	Class: II
Divisions: 1 & 2	Division: 1 & 2
Group: D	Groups: F & G

DIMENSIONS:

Length	Width	Height	Weight
27" (68.5 cm)	10" (25.4 cm)	15" (38.1 cm)	122 lbs. (55.33 kg)