



SPECIFICATIONS

Product Description: **SOURCE PRE-FILTER**
 Part Number: **9350-03**
 Style: **REMOTE**

GENERAL DESCRIPTION:

Where air quality is especially low, this free-standing or wall-mounted particulate assembly helps extend the life of the filter panel's disposable filters by removing liquids and contaminants down to 5 microns. It is equipped with an adjustable high pressure regulator and gauge to meet the NIOSH requirement for point-of-attachment.



CONSTRUCTION:

Stand: Powder coated steel
 Relief valve: Brass, spring loaded (External)
 Max Temperature: 150° F (65.5° C)
 Maximum pressure: 250 psi (17.2 bar)
 Flow Capacity: 165 CFM (280.33 m3/hr)
 Fittings: ½" (1.27 cm) Quick-Connect Hansen

REGULATOR & MANIFOLD:

Manifold: Zinc
 Adjusting knob: Acetal
 Body Cap: ABS
 Valve: Balanced Valve Design, Brass/Nitrile
 Diaphragm: Spring loaded, Nitrile/Zinc
 Pressure gauge: Analog, 0-300 psi (0-20.69 bar), 2" (5.08 cm) diameter

FILTRATION BOWL:

Bowl: Zinc, with a Polycarbonate sight gauge
 Element retainer: Acetal
 Useful Retention: 2.87 oz. (81.36 g)
 Seal: Nitrile

FILTER ELEMENT:

Standard Filtration: 5 Micron
 Element Type: Particulate
 Material: Sintered Polyethylene
 Drain: Automatic mechanical with float

DIMENSIONS:

Depth	Width	Height	Weight
9" (22.8 cm)	6 ¼" (15.8 cm)	13 15/16" (35.4 cm)	3.5 lbs. (1.6 kg)