



## SPECIFICATIONS

Product Description: **EXTENSION CORD**  
 Part Number: **9540-50**  
 Style: **STANDARD**

### GENERAL DESCRIPTION:

This extra heavy duty cord powers 15 AMP, 125V. Weather resistant from -40° F to 167° F (-40° C to 75° C) with rugged and durable clear molded plugs. Outer jacket is flame, water and oil resistant. This cord meets OSHA specifications and is UL listed.

### TECHNICAL SPECS:

Cord: 50' (15.24 m), 12/3 AWG, 15A  
 Plug: NEMA 5-15P  
 Connector: NEMA 5-15R  
 Temp.: -40° F to 167° F (-40° C to 75° C)  
 Weight: 5.9 lbs. (2.68 kg)  
 Color: Yellow/Black Stripe



Product Description: **EXTENSION CORD**  
 Part Number: **9540-50EX, 9540-60EX (220V)**  
 Style: **EXPLOSION-PROOF**

### GENERAL DESCRIPTION:

The 50' extension cord comes with a 20 AMP connector and plug. The weather resistant cord has a temperature range of -40° F to 221° F (-40° C to 105° C), is flexible and provides excellent abrasion resistance. Both the plug and receptacle have CSA Certifications for: Class I Division 1 & 2 Groups B, C, and D; Class II, Division 1 & 2 Groups F\* and G.

### TECHNICAL SPECS:

Cord: 50' (15.24 m), 10/3 AWG, 30A  
 Plug: NEMA 20A, 1 HP, Explosion-Proof  
 Connector: 125VAC, 20A w/ spring cover (PN 9540-50EX)  
 220VAC, 20A w/ spring cover (PN 9540-60EX)  
 Temp.: -40° F to 221° F (-40° C to 105° C)  
 Weight: 15.5 lbs. (7.03 kg)  
 Color: Black



### HAZARDOUS LOCATION RATING:

Class: I	Class: II
Division 1 & 2	Division 1 & 2
Groups B, C and D	Groups F* and G

\*Do not use where electrically conductive dusts are present (most coal dust is not electrically conductive)