



## SPECIFICATIONS

Product Description: **VENTILATION BLOWER, HIGH OUTPUT, EXPLOSION-PROOF**  
 Part Number: **9515-50EXE**  
 Style: **AXIAL FAN 16" (40.6 cm), 230V, 50/60Hz**

### GENERAL DESCRIPTION:

Designed for applications requiring a maximum amount of output. Made from 16-gauge cold rolled steel housing and powder-coated in safety orange with 3 blade impeller. Powered by a 1 ½ hp, 2875-3450 RPM UL listed, IECEX/ATEX/INMETRO certified motor. Comes with an interchangeable flange for intake or exhaust mounting, integrated carry handles for easy transport and a steel/zinc plated grill. Four rubber feet, built in on/off switch and voltage change switch are added features of this powerhouse unit.



### CONSTRUCTION:

- Complete unit epoxy powder-coated in orange
- Interchangeable flange for intake or exhaust side mounting
- 16-gauge cold rolled steel housing
- Integrated carry handles
- Steel grill (zinc plated), equipped with four rubber feet
- Built-in "on/off" switch
- Ducting grounding lug
- *NOTE: EX blowers require an explosion-proof socket (110V: 9503-03, 220V: 9506-06)*

### MOTOR:

HP: 1 ½ HP  
 Certifications: UL Listed, IECEX/ATEX/INMETRO Certified  
 Voltage/Hz: 115V/230V AC, 50/60Hz, Single Phase, (all world motor with voltage selector switch)  
 RPM: 2875/3450  
 Current Draw: 19.3/9.6 (50 Hz), 15.5/7.8 (60 Hz)  
 Cord: 25' (7.62 m) 12/3 AWG, MTW 90C 600V  
 Protection: Thermal, Automatic Reset  
 Plug: Not supplied


### FAN:

- Anti-Static glass reinforced polyamide (PAGAS) three blade fan with aluminum hub

### ACCESSORIES:

#### Ducting

- Black, single-ply, neoprene coated, statically conductive vinyl/polyester material, temp. resistant up to 250° F (121.1° C)
- Retractable, non-collapsible design, Class 1 hard drawn spring steel wire helix (meets ASTM 227 specs)
- Grounding cable on both ends
- **WARNING:** When using statically conductive ducting, the integrated grounding wire must be properly grounded to the blower chassis OR linked to any additional grounding wire or duct used (as shown). Refer to User Manual for detailed instructions.



#### EX Rated Receptacles/Plugs

- NEC 505 or IECEX/ATEX available (consult factory)

### HAZARDOUS LOCATION RATING:

#### Motors

ATEX	II 2 G Ex d Gb
IECEX	Ex d IIB Gb
INMETRO	Ex d IIB Gb

### BLOWER DIMENSIONS:

Length	Width	Height	Weight
18" (45.7 cm)	18" (45.7 cm)	19" (48.2 cm)	62 lbs. (28.12 kg)

### \*FLOW RATES: (CFM calculated using 15' (4.57 m) of 16" (40.6 cm) ducting)

Free Air	One 90° Bend	Two 90° Bends
4839 CFM (8226.30 m³/hr)	2942 CFM (5001.40 m³/hr)	2926 CFM (4974.20 m³/hr)

\*Air flow determined at 60 Hz