



SPECIFICATIONS

Product Description: **SOCKET**
Part Number: **9503-03, 9503-06**
Style: **EXPLOSION-PROOF**

GENERAL DESCRIPTION:

This explosion-proof socket is used in hazardous locations. Features an iron mounting box with triple coat finish and a spring-loaded door keeping dust out of receptacle when plug is not in use. When plug is in use, a neoprene gasket inside receptacle seals around plug keeping out dirt, water, dust and other foreign matter.



TECHNICAL SPECS:

Certifications: UL listed, CSA certified
Plug: NEMA 20A, Explosion-Proof
1 HP (9503-03)
2 HP (9503-06)
Connector: 125V AC, 20A w/ spring cover (9503-03)
220V AC, 20A w/ spring cover (9503-06)
Poles/Wires: 2P3W Grounding
Door: Spring Door
Box: 1-Gang
Hubs: (1) 1/2"
Dimensions: 3 3/16" L x 6 3/16" W x 6 1/4" H
Material: Aluminum, Malleable Iron
Color: Gray

HAZARDOUS LOCATION RATING:

Class: I	Class: II
Division 1 & 2	Division 1 & 2
Groups B, C and D	Groups F* and G

****Do not use where electrically conductive dusts are present (most coal dust is not electrically conductive)***