

SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE**
 Part Number: **9550-15EX, 9550-25EX**
 Style: **12" (30.4 cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable, and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.



CONSTRUCTION:

- Vinyl and polyester anti-static materials
- Single ply
- Neoprene-coated
- Temperature resistant up to 250° F (121° C)
- Retractable, non-collapsible design
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- Meet flame retardant requirements of UL-94-V0
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end

AVAILABLE:

PN	Diameter	Length	End-Straps
9550-15EX	12" (30.4 cm)	15' (4.57 m)	Dual
9550-25EX	12" (30.4 cm)	25' (7.62 m)	Dual

ACCESSORIES:

PN	Ducting Size	Description
9550-01	12" (30.4 cm)	Duct to duct connector with raised lip
9600-36	12" (30.4 cm)	Storage rack for 12" (30.4 cm) ducting up to 25' (7.62 m) ducting
9600-45	12" (30.4 cm)	Duct storage bag