

SPECIFICATIONS

Product Description: **16" (40.6 cm) AXIAL DC PLASTIC BLOWER**
 Part Number: **9556, 9556-15, 9556-25**
 Style: **WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

Lightweight, portable, and durable, this DC blower has a ½ HP motor with an efficient six-blade impeller in a rugged housing. Suited for confined spaces such as tanks, or utility sites. The quick-connect system allows workers to attach the canister, tools free, to the input side for powerful extraction or output side for ventilation. This unit is constructed to be powered by a 12V car or truck battery for portable convenience.

CONSTRUCTION:

- Polyethylene housing, in "safety orange"
- Lightweight, corrosion-, UV- and chemical-resistant
- Super quiet
- Carry handle molded into blower and canister housing
- Black plastic grills
- 15' (4.57 m) power cord with heavy duty battery clamps
- Easily accessible inline fuse

MOTOR:

HP: ½ HP
 Voltage: 12V DC
 RPM: 1750
 Amps: 39A
 Fuse: 60A

FAN:

- Glass reinforced polypropylene (PPG), six-blade fan with aluminum hub

DUCTING: (included on 9556-15 and 9556-25 models)

- Retractable, non-collapsible design, Single ply
- PVC coated vinyl and polyester materials
- Yellow color with black weather strip and integrated nylon attachment strap
- Spring steel wire helix

BLOWER DIMENSIONS:

PN	Length	Width	Height	Weight
9556	20" (50.8 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	48 lbs. (21.8 kg)
9556-15	34" (86.4 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	74 lbs. (33.6 kg)
9556-25	34" (86.4 cm)	22.5" (57.1 cm)	22.5" (57.1 cm)	81 lbs. (36.7 kg)

FLOW RATES: (CFM calculated using 15' (4.57 m) of 16" (40.6 cm) ducting)

Free Air	One 90° Bend	Two 90° Bends
2359 CFM (4008 m ³ /hr)	1666 CFM (2831 m ³ /hr)	1587 CFM (2696 m ³ /hr)

