

## SPECIFICATIONS

Product Description: **SOURCE PRE-FILTER**  
Part Number: **9350-03**  
Style: **REMOTE**

### GENERAL DESCRIPTION:

Where air quality is especially low, this free-standing or wall-mounted particulate assembly helps extend the life of the filter panel's disposable filters by removing liquids and contaminants down to 5 microns. It is equipped with an adjustable high-pressure regulator and gauge to meet the NIOSH requirement for point-of-attachment.

### CONSTRUCTION:

Stand: Powder coated steel  
Relief valve: Brass, spring loaded (External)  
Max Temperature: 150° F (65.5° C)  
Maximum pressure: 250 psi (17.2 bar)  
Flow Capacity: 165 CFM (280.33 m<sup>3</sup>/hr)  
Fittings: ½" (1.27 cm) Quick-Connect Hansen



### REGULATOR & MANIFOLD:

Manifold: Zinc  
Adjusting knob: Acetal  
Body Cap: ABS  
Valve: Balanced Valve Design, Brass/Nitrile  
Diaphragm: Spring loaded, Nitrile/Zinc  
Pressure gauge: Analog, 0-300 psi (0-20.69 bar), 2" (5.08 cm) diameter

### FILTRATION BOWL:

Bowl: Zinc, with a Polycarbonate sight gauge  
Element retainer: Acetal  
Useful Retention: 2.87 oz. (81.36 g)  
Seal: Nitrile

### FILTER ELEMENT:

Standard Filtration: 5 Micron  
Element Type: Particulate  
Material: Sintered Polyethylene  
Drain: Automatic mechanical with float

### DIMENSIONS:

Depth	Width	Height	Weight
9" (22.8 cm)	6 ¼" (15.8 cm)	13 15/16" (35.4 cm)	3.5 lbs. (1.6 kg)