

SPECIFICATIONS

Product Description: **BREATHING AIR PUMP A300**
 Part Number: **9806**
 Style: **ROTARY VANE**

GENERAL DESCRIPTION:

Portable & light weight air source, designed for one full or half face respirator user. Solid performance in applications such as painting, cleaning, or chemical handling operations.



CONSTRUCTION:

- Rigid metal base & housing
- Brass plumbing
- Quick-connect Rectus (OBAC) air fitting
- Adjustable brass pressure relief valve
- Powder-coated blue

PUMP:

**Warning: Breathing Air Pumps are not to be used with generators*

***Warning: Air inlet to the pump must be located where breathable air can be assured at all times*

Type: Oil-less, rotary vane
 Vanes: Carbon construction (4 ea./ replaceable)
 (1.25" (3.1 cm) X 1.50" (3.8 cm) X 0.125" (0.31 cm)
 Inlet Filter: 40.0 Micron bronze/steel
 Exhaust Filter: 0.30 Micron HEPA inline
 Pressure Gage: 1½" (3.8 cm) face, (0-15 psi) (0-1.03 bar), steel housing
 Working Press: 2-12 psi (0.14-0.83 bar) (15 psi (1.03 bar) Max)
 Performance: 0-5 CFM (0-8.5 m³/hr) @ 60 Hz, 0-4 CFM (0-6.79 m³/hr) @ 50 Hz
 Noise level at pump: 90 dB
 At 6 feet (1.82m): 74 dB
 At 10 feet (3.04m): 72 dB
 Temperature Range: 32° F to 104° F (0° C to 40° C)

MOTOR:

HP: 1/4 HP
 Volts: 115/230V AC, Single Phase
 Hertz: 50/60
 Certifications: UL Recognized, CSA Certified
 RPM: 1725 RPM @ 60Hz / 1425 RPM @ 50 Hz
 Current Draw: 115V, 4.4A @ 60 Hz / 4.4A @ 50Hz
 Current Draw: 230V, 2.2A @ 60Hz / 2.5A @ 50Hz
 Cord: 6.5' (1.98 m) AWG 16/3 SJOOW with integrated ON/OFF switch
 Plug: Integrated NEMA 5-15

AIRLINE:

100' (30.4 m) max from pump to respirator (sold separately)

DIMENSIONS:

Length	Width	Height	Weight
13" (33.0 cm)	6.25" (15.8 cm)	12" (30.5 cm)	30 lbs. (13.6 kg)