

# **SPECIFICATIONS**

Product Description: HOOD, SUPPLIED AIR

Part Number: 9912-C

Style: DOUBLE BIB, FULLY DISPOSABLE TYVEK® w/ PERSONAL AIR COOLER

#### **GENERAL DESCRIPTION:**

Made of poly-coated Tyvek material, this hood offers the increased protection of two bibs. The inner bib tucks inside protective garments so air flows down for a cooling effect on the body, and the outer bib secures under the arms with hook and loop to keep the hood from rising. The hood features an extra-large lens for better visibility. It offers the same convenient design with down tube and suspension built in, making the complete hood fully disposable. **NIOSH approved!** 

#### HOOD:

- Poly-coated DuPont Tyvek
- Splash resistant hood and bibs
- · Seams surged to seal in the air flow
- Generous size is ideal for workers with beards or goggles

### **SUSPENSION:**

- Disposable one-piece assembly
- · Absorbent foam headband
- Adjustable hook and loop closure head harness secures hood in place

#### **DOWNTUBE:**

- Multi-layer foam sound dampening system to prevent crushing and twisting during use
- Meets stringent NIOSH requirements for sound levels inside a hood
- Located behind the hood allowing it to be out of the way

## LENS:

- Clear co-polyester, (PETG) 15 mil, 6" X 12" (15.2 cm x 30.4 cm)
- Distortion-free with panoramic view

# LENS PEEL OFFS: (PN 9910-25) (optional)

• Co-Polyester, clear film with adhesive backing, 5¼" X 11¼" (13.3 cm x 28.57 cm) (0.007" (0.017cm) thick)

Hose				Hood Used with		
Part No	Length	Fitting		Controllers	Approval No	
Low Pressure				Low Pressure		
9100-25	25' (7.62 m)	OBAC-Brass		9910-11 Low Pressure Flow Adapter	TC-19C-331	
9100-50	50' (15.24 m)	OBAC-Brass				
9100-100	100' (30.4 m)	OBAC-Brass				
High Pressure				High Pressure		
9101-25B	25' (7.62 m)	Hansen-Brass		9992 Control Valve	TC-19C-357	
9101-50B	50' (15.24 m)	Hansen-Brass		9991 Cooler	TC-19C-357	
9101-100B	100' (30.4 m)	Hansen-Brass		9990 Temperature Controller	TC-19C-357	

1360 Shiloh Church Road Piedmont, SC 29673 864-846-8740 800-622-3530 FAX: 800-362-7231 <u>www.allegrosafety.com</u>

Rev B 1-26-23